

# HYDRO SYSTEMS

## I23-I33-223 HOUSINGS



Most economical three pieces style filter cartridge housings can be used in a broad range of residential, commercial and industrial applications. Accepts standard length in 2" 1/2 OD standard, 5" - 10" and 20". Rugged corrosion resistant material used to provide long trouble free life.

Sumps available clear by SAN and opaque white by Polypropylene

### THREE PIECE DESIGN FOR BEST ECONOMY.

PUSH BOTTON VENT ALLOWS PRESSURE RELIEF AND AIR BLEEDING. (optional without pressure vent bottom).

- Food grade material made
- Max working pressure 100psi (6,9 bar)
- Max working temperature 100°F ( 38°C)
- 1/4" - 3/8" - 3/4" -1" NPT BRASS INSERTS port size



## I23-I33-223 HOUSINGS

MODELS	DESCRIPTION	DIMENSIONS	MAX PRESSURE DROP
223-5124	housing with opaque white sump, for 4"7/8 cartridges	7,20" x 4,9"	1 psdi @ 4 gpm
223-52524	housing with clear sump, for 4"7/8 cartridges	7,20" x 4,9"	1 psdi @ 4 gpm
223-3135	housing with opaque white sump, for 10" cartridges	11,7" x 4,9"	2 psid @ 8 gpm
223-3235	housing with clear sump, for 10" cartridges	11,7" x 4,9"	2 psid @ 8 gpm
223-4135	housing with opaque white sump, for 20" cartridges	23,6" x 4,9"	3 psdi @ 12 gpm
223-4235	housing with clear sump, for 20" cartridges	23,6" x 4,9"	3 psdi @ 12 gpm



*Tested and Certified by NSF International against NSF /ANSI Standard 42 for materials and structural integrity requirements.*

# HYDRO SYSTEMS

## I02 HOUSINGS



Economical filter cartridge housings can be used in a broad range of residential, commercial and industrial applications. Accepts standard length in 2"1/2 OD standard, 5" - 10" and 20". Rugged corrosion resistant material used to provide long trouble free life.

Sumps available clear by SAN and opaque white by Polypropylene

### TWO PIECE DESIGN FOR BEST ECONOMY.

**PUSH BOTTON VENT ALLOWS PRESSURE RELIEF AND AIR BLEEDING.** (optional without pressure vent bottom).

- Food grade material made
- Max working pressure 100psi (6,9 bar)
- Max working temperature 100°F ( 38°C)
- 1/4" - 3/8" - 3/4" NPT PLASTIC port size

## I02 HOUSINGS

MODELS	DESCRIPTION	DIMENSIONS	PRESSURE (drop <sup>(1)</sup> max)
I02-5124	housing with opaque white sump, for 4"7/8 cartridges	7" x 4,9"	1 psdi @ 4 gpm
I02-5224	housing with clear sump, for 4"7/8 cartridges	7" x 4,9"	1 psid @ 4 gpm
I02-1124	housing with opaque white sump, for 10" cartridges	12,4" x 4,9"	2 psid @ 8 gpm
I02-1224	housing with clear sump, for 10" cartridges	12,4" x 4,9"	2 psid @ 8 gpm
I02-2124	housing with opaque white sump, for 20" cartridges	22,5" x 4,9"	3 psdi @ 12 gpm

*Tested and Certified by NSF International against NSF/ANSI Standard 42 for materials and structural integrity requirements.*

