

HYDRO SYSTEMS I13 HOUSINGS



Professional filter cartridge housings can be used in a broad range of residential, commercial and industrial applications. Accept standard length in 2" 1/2 OD standard. Rugged corrosion resistant materials used long trouble free life. Sumps available clear by Polycarbonate or SAN and opaque white by Polypropylene

THREE PIECE DESIGN WITH RING NUT FEATURE ALLOWS FOR QUICK & EASY ASSEMBLY. PUSH BOTTON VENT ALLOWS PRESSURE RELIEF AND AIR BLEEDING.

- Food grade material made
- Max working pressure 100psi (6,9 bar)
- Max working temperature 100°F (38°C)
- 3/4" - 1" NPT port size (plastic / Brass inserts / AISI 304L inserts)
- Mounting brackets & wrenches

I13 HOUSINGS

MODELS	DESCRIPTION	DIMENSIONS	MAX PRESSURE DROP
I13-3135	housing with opaque white sump, for 10" cartridges	12,5" x 5,3"	2 psid @ 8 gpm
I13-3235	housing with clear sump, for 10" cartridges	12,5" x 5,3"	2 psid @ 8 gpm
I13-4135	housing with opaque white sump, for 20" cartridges	22,6" x 5,3"	3 psdi @ 12 gpm
I13-4235	housing with clear sump, for 20" cartridges	22,6" x 5,3"	3 psdi @ 12 gpm



Tested and Certified by NSF International against NSF/ANSI Standard 42 for materials and structural integrity requirements.

HYDRO SYSTEMS

I20 BYPASS HOUSINGS



Professional filter cartridge housings can be used in a broad range of residential, commercial and industrial applications. Accept standard length in 2" 1/2 OD standard. rugged corrosion resistant materials used long trouble free life. Sumps available clear by Polycarbonate or SAN and opaque white by Polypropylene

**VALVE IN HEAD DESIGN OFFER THREE POSITION:
FILTER - OFF - BYPASS MODES.**

**THREE PIECE DESIGN WITH RING NUT FEATURE ALLOWS FOR QUICK & EASY ASSEMBLY.
AUTO PRESSURE VENTING RELIEF, TURNING THE SELECTOR BY PASS VALVE.**

- Food grade material made
- Max working pressure 100 psi (6,9 bar)
- Max working temperature 100°F (38° C)
- 3/4" - 1" NPT port size (plastic / Brass inserts / AISI 304 L inserts)
- Mounting brackets & wrenches

I20 BYPASS HOUSINGS

MODELS	DESCRIPTION	DIMENSIONS	MAX PRESSURE DROP
I20-3155	housing with opaque white sump, for 10" cartridges	13,3" x 5,5"	4 psid @ 8 gpm
I20-3255	housing with clear sump, for 10" cartridges	13,3" x 5,5"	4 psid @ 8 gpm
I20-4155	housing with opaque white sump, for 20" cartridges	23,4" x 5,5"	6 psdi @ 12 gpm
I20-4255	housing with clear sump, for 20" cartridges	23,4" x 5,5"	6 psdi @ 12 gpm



Tested and Certified by NSF International against NSF /ANSI Standard 42 for materials and structural integrity requirements.