

# HYDRO SYSTEMS

## I 13 HOUSINGS



Professional filter cartridge housings can be used in a broad range of residential, commercial and industrial applications. Accept standard length in 2" 1/2 OD standard. Rugged corrosion resistant materials used long trouble free life. Sumps available clear by PET, Polycarbonate or SAN and opaque white by Polypropylene

**THREE PIECE DESIGN WITH RING NUT FEATURE ALLOWS FOR QUICK & EASY ASSEMBLY. PUSH BOTTON VENT ALLOWS PRESSURE RELIEF AND AIR BLEEDING.**

- Food grade material made
- Max working pressure 125 psi (8,6 bar)
- Max working temperature 100°F (38°C)
- 3/4" - 1" NPT port size (plastic / Brass inserts / AISI 304L inserts)
- Mounting brackets & wrenches

### I 13 HOUSINGS

MODELS	DESCRIPTION	DIMENSIONS	MAX PRESSURE DROP
I13-3135	housing with opaque white sump, for 10" cartridges	12,5" x 5,3"	2 psid @ 8 gpm
I13-3235	housing with clear sump, for 10" cartridges	12,5" x 5,3"	2 psid @ 8 gpm
I13-4135	housing with opaque white sump, for 20" cartridges	22,6" x 5,3"	3 psdi @ 12 gpm
I13-4235	housing with clear sump, for 20" cartridges	22,6" x 5,3"	3 psdi @ 12 gpm



*Tested and Certified by NSF International against NSF /ANSI Standard 42 for materials and structural integrity requirements.*