

HYDRO SYSTEMS

I02 HOUSINGS



Economical filter cartridge housings can be used in a broad range of residential, commercial and industrial applications. Accepts standard length in 2"1/2 OD standard, 5" - 10" and 20". Rugged corrosion resistant material used to provide long trouble free life.

Sumps available clear by SAN and opaque white by Polypropylene

TWO PIECE DESIGN FOR BEST ECONOMY.

PUSH BOTTON VENT ALLOWS PRESSURE RELIEF AND AIR BLEEDING. (optional without pressure vent bottom).

- Food grade material made
- Max working pressure 100psi (6,9 bar)
- Max working temperature 100°F (38°C)
- 1/4" - 3/8" - 3/4" NPT PLASTIC port size

I02 HOUSINGS

MODELS	DESCRIPTION	DIMENSIONS	PRESSURE (drop ⁽¹⁾ max)
I02-5124	housing with opaque white sump, for 4"7/8 cartridges	7" x 4,9"	1 psdi @ 4 gpm
I02-5224	housing with clear sump, for 4"7/8 cartridges	7" x 4,9"	1 psid @ 4 gpm
I02-1124	housing with opaque white sump, for 10" cartridges	12,4" x 4,9"	2 psid @ 8 gpm
I02-1224	housing with clear sump, for 10" cartridges	12,4" x 4,9"	2 psid @ 8 gpm
I02-2124	housing with opaque white sump, for 20" cartridges	22,5" x 4,9"	3 psdi @ 12 gpm

Tested and Certified by NSF International against NSF/ANSI Standard 42 for materials and structural integrity requirements.

