

HYDRO SYSTEMS

123-133-223 HOUSINGS



Most economical three pieces style filter cartridge housings can be used in a broad range of residential, commercial and industrial applications. Accepts standard length in 2" 1/2 OD standard, 5" - 10" and 20". Rugged corrosion resistant material used to provide long trouble free life. Sumps available clear by PET or SAN and opaque white by Polypropylene

THREE PIECE DESIGN FOR BEST ECONOMY.
PUSH BOTTON VENT ALLOWS PRESSURE RELIEF AND AIR BLEEDING. (optional without pressure vent bottom).

- Food grade material made
- Max working pressure 125 psi (8,6 bar)
- Max working temperature 100°F (38°C)
- 3/4" - 1" NPT BRASS INSERTS port size
- 1/4" - 3/8" - 3/4" - 1" NPT PLASTIC port size



123-133-223 HOUSINGS

MODELS	DESCRIPTION	DIMENSIONS	MAX PRESSURE DROP
223-5124	housing with opaque white sump, for 4"7/8 cartridges	7,20" x 4,9"	1 psdi @ 4 gpm
223-5224	housing with clear sump, for 4"7/8 cartridges	7,20" x 4,9"	1 psdi @ 4 gpm
223-3135	housing with opaque white sump, for 10" cartridges	11,7" x 4,9"	2 psid @ 8 gpm
223-3235	housing with clear sump, for 10" cartridges	11,7" x 4,9"	2 psid @ 8 gpm
223-4135	housing with opaque white sump, for 20" cartridges	23,6" x 4,9"	3 psdi @ 12 gpm
223-4235	housing with clear sump, for 20" cartridges	23,6" x 4,9"	3 psdi @ 12 gpm



Tested and Certified by NSF International against NSF /ANSI Standard 42 for materials and structural integrity requirements.