

HYDRO SYSTEMS

I34 JUMBO HOUSINGS



Professional filter cartridge housings series suitable for high-flow and for high capacity applications. Accept standard length in 4"1/2 OD standard. Rugged corrosion resistant materials used long trouble free life. Sumps available clear by PET or Polycarbonate and opaque white by Polypropylene

THREE PIECE DESIGN WITH RING NUT FEATURE ALLOWS FOR QUICK & EASY ASSEMBLY.
PUSH BOTTONVENT ALLOWS PRESSURE RELIEF AND AIR BLEEDING.
PREMIUM BOTTOM SUMP DRAIN PORT

- Food grade material made
- Max working pressure 87 psi (6,9 bar)
- Max working temperature 100°F (38°C)
- 3/4" - 1" - 1" 1/2 NPT PLASTIC port size
- 3/4" - 1" - 1" 1/2 NPT with brass or AISI304L inserts
- Heavy duty metal mounting bracket

I34 JUMBO HOUSINGS

MODELS	DESCRIPTION	DIMENSIONS	MAX PRESSURE DROP
134-3135	housing with opaque white sump, for 10" cartridges	15,4" x 8"	1 psid @ 10 gpm
134-3235	housing with clear sump, for 10" cartridges	15,4" x 8"	1 psid @ 10 gpm
134-4135	housing with opaque white sump, for 20" cartridges	25,4" x 8"	1 psid @ 10 gpm
134-4235	housing with clear sump, for 20" cartridges	25,4" x 8"	1 psid @ 10 gpm

Tested and Certified by NSF International against NSF /ANSI Standard 42 for materials and structural integrity requirements.

