

# HYDRO SYSTEMS

## I36 JUMBO BP HOUSINGS



Professional filter cartridge housings series suitable for high-flow and for high capacity applications. Accept standard length in 4" 1/2 OD standard. Rugged corrosion resistant materials used long trouble free life.

Sumps available clear by PET or Polycarbonate and opaque white by Polypropylene.

**VALVE IN HEAD DESIGN WITH THREE OPERATIONAL POSITIONS:**

**FILTER - OFF - BYPASS MODES.**

**THREE PIECE DESIGN WITH RING NUT FEATURE ALLOWS FOR QUICK & EASY ASSEMBLY.**

**PUSH BOTTOM VENT ALLOWS PRESSURE RELIEF AND AIR BLEEDING.**

**PREMIUM BOTTOM SUMP DRAIN PORT**

- Food grade material made
- Max working pressure 87 psi (6 bar)
- Max working temperature 100°F (38°C)
- 3/4"- 1" 1 1/2 NPT plastic port size
- Heavy duty metal mounting bracket

### I36 JUMBO BP HOUSINGS

MODELS	DESCRIPTION	DIMENSIONS	MAX PRESSURE DROP
I36-3135	housing with opaque white sump, for 10" cartridges	16" x 8"	2 psid @ 10 gpm
I36-3235	housing with clear sump, for 10" cartridges	16" x 8"	2 psid @ 10 gpm
I36-4135	housing with opaque white sump, for 20" cartridges	26" x 8"	2 psid @ 10 gpm
I36-4235	housing with clear sump, for 20" cartridges	26" x 8"	2 psid @ 10 gpm

*Tested and Certified by NSF International against NSF /ANSI Standard 42 for materials and structural integrity requirements.*

